SAFETY DATA SHEET



1. Identification

Product identifier PENNCOAT™ 101

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Armor Limited, Inc.

Address 2410 US-15 South, Sumter, SC 29150

After hours telephone 1-877-982-7667

number

Normal work hours 1-877-982-7667

telephone number

Website www.armor-inc.com

E-mail customerservice@armor-inc.com

Emergency 24-hour telephone number Information on

operation hours

CHEMTREC North America: 800-424-9300, International: +1-703-527-3887

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 1
Serious eye damage/eye irritation Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

No hazards resulting from the material as supplied.

Label elements



Signal word Danger

Hazard statement Harmful if inhaled. Causes severe skin burns and eye damage. Causes serious eye irritation.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective

clothing/eye protection/face protection. Wash thoroughly after handling. Use only outdoors or

in a well-ventilated area.

Response IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/take off

immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If eye irritation persists: Get medical advice/attention. Call a poison center/doctor if you feel

unwell. Specific treatment see Section 4 of this SDS.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Material name: PENNCOAT™ 101 5587 Version #: 01 Issue date: 02-14-2025 Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	100

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. Call a physician if symptoms develop or persist.

Skin contact If molten asphalt strikes exposed skin, cool immediately by quenching with cold water. Ice or

> cold packs may be used in the event water is unavailable. Lotion or hand cream may aid in the removal of asphalt. If clothing sticks to the skin, do not remove. Wash contact areas with soap

and water. If needed, seek medical attention.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and

persists.

Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to a victim who is Ingestion

unconscious or is having convulsions. If ingestion of a large amount does occur, call a poison

control center immediately.

Most important symptoms/effects, acute

and delayed

Choking. Difficulty in breathing. Skin irritation. Causes serious eye irritation. Diarrhea. Nausea, vomiting. Defatting of the skin. Dermatitis. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Exposed individuals may experience eye tearing, redness, and discomfort.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information**

protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Foam. Dry chemical powder. Carbon dioxide (CO2). Water fog.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed. Carbon oxides.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use of foam or water may

cause frothing.

Specific methods In the event of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: PENNCOAT™ 101

5587 Version #: 01 Issue date: 02-14-2025

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike far ahead of spill for later disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the

SDS.

Environmental precautions Avoid

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid contact with molten material. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S. - NIOSH

ComponentsTypeValueASPHALT, OXIDIZED (CAS 64742-93-4)REL 5 mg/m3

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles and face shield are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Thermally protective, chemical resistant gloves are

recommended. If contact with forearms is likely, wear gauntlet style gloves.

Other Use of an impervious apron is recommended. Wear appropriate clothing to prevent any

possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Brown to black in color.

Physical state Solid.

Form Solid. Semi-solid at ambient temperature

Color
Black.
Tar-like
Odor threshold
Not available.
PH
Not available.
Melting point/freezing point
Not available.

Material name: PENNCOAT™ 101

Initial boiling point and

boiling range

Not available.

Flash point

>525.0 °F (>273.9 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Not available. Vapor density **Relative density** Not available.

Solubility(ies)

Solubility (water) Insoluble **Partition coefficient** Not available. (n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Viscosity Not available.

Other information

Not explosive. **Explosive properties** Oxidizing properties Not oxidizing.

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Stable under normal temperature conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials Strong oxidizing agents. Acids.

Hazardous decomposition

products

Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes severe skin burns and eye damage.

Eye contact Causes serious eye irritation. **Ingestion** May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Choking. Diarrhea. Nausea, vomiting. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dermatitis. Defatting of the skin. Difficulty in breathing. Exposed

individuals may experience eye tearing, redness, and discomfort.

Information on toxicological effects

Acute toxicity Harmful if inhaled. May be harmful if swallowed. Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Material name: PENNCOAT™ 101 SDS US 4/7

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

Not available.

single exposure

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA

waste under 40 CFR 261. Allow molten resin to solidify before disposal.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues /

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: unused products

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container

is emptied. Empty containers should be taken to an approved waste handling site for recycling

or disposal.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act

All components of the mixture on the TSCA 8(b) inventory are designated "active". (TSCA)

Material name: PENNCOAT™ 101 SDS US

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Classified hazard Acute toxicity (any route of exposure)

categories Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to ASPHALT, OXIDIZED, which is known to the State of California

to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT, OXIDIZED (CAS 64742-93-4) Listed: January 1, 1990

International Inventories

Country(s) or region	Inventory name On inventory (yes/	no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe European Inventory of Existing Commercial Chemical Substances (EINECS)		Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the		

16. Other information, including date of preparation or last revision

Issue date 02-14-2025

Version # 01

governing country(s).

Material name: PENNCOAT™ 101

Further information

HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings

Health: 3 Flammability: 0 Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Armor cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

5587 Version #: 01 Issue date: 02-14-2025

Material name: PENNCOAT™ 101 SDS US 7/7